

QUALITY GARAGE FLOORING

MATERIALS & COLORS

Beautify and protect your garage with high-quality hybrid epoxy floor coatings. Low-maintenance epoxy floors are resistant to stains, spills and harsh, concrete-damaging winter salts. Choose from an array of colors and textures, including three solid colors and 11 flake colors — all with a high-gloss shine. With an install time of only two days, class-leading materials and polished good looks, our epoxy floor coatings will bring style and durability to your garage for years to come.

MATERIALS: All of our epoxy floor systems use a three-layer application process for performance and longevity. Finished floors are slip-resistant with a high-gloss shine.

Base/top layer: Double the thickness of competing products, our floor coatings are easy to maintain and will not chip, peel or yellow. Our products are backed by a oneyear manufacturer's warranty.

Flake/color layer: Colored polymer I/4" flake flooring, available in 11 colors. For a different look, Desert, Graphite, Scottsdale, Sedona and Smoke flake are also available in a smaller 1/8" texture.



All II chip colors are available in 1/4" flake, 1/8" flake available where shown.



Camouflage Blue Ice



Desert (1/4", 1/8")



Graphite (1/4", 1/4")



Mojave

Quartzite








Silverado

Scottsdale (1/4", 1/8") Sedona (1/4", 1/8")

COMPARISON

SUPERIOR FINISH

Our hybrid epoxy base coat is twice as thick and cures harder than other materials.



Competitors' coatings are more likely to chip and peel.

THEIRS

Competitors' floors can yellow from the sun and lights.

STAIN RESISTANT

Oils and spills are easy to wipe up or hose off with our low-maintenance flooring.





100% UV PROTECTED

Our floor coatings are 100% UV protected and will not fade or yellow over time.





Terra Cotta

	OUR PRODUCTS	COMPETING PRODUCTS
MAINTENANCE	Everyday dirt and grime are easily hosed off. Motor oil and spills wipe up with mild detergent. Harsh salts do not harm the floor coatings.	Other products trap dirt creating a mainte- nance headache. Motor oils and spills will stain and harsh salts will deteriorate the floor coating.
YELLOWING	100% UV protection means the flooring will remain clear and free of ambering or yellowing.	No UV protection allows the floor to fade and discolor from indoor lighting and sunlight.
THICKNESS	On average, our floor coatings are twice as thick as other products which creates a more durable floor and provides an ample base for even chip coverage.	Thin base coats are prone to yellowing, peeling and chipping and leave up to 20% of the concrete showing through the base coat.
FINISH	Our hybrid epoxy cures harder than standard epoxy producing higher impact and abrasion resistance.	Softer epoxies are prone to scrapes, chips and "paw printing" by hot tires.
CURE TIME	Quick cure times allow for foot traffic within 24 hours of installation and vehicle weight after 72 hours.	Longer cure times between coatings equate to a wait time of up to seven days.
INSTALLATION	Floors are mechanically profiled to ensure a superior bond between the concrete floor and the coating.	Out-dated methods may cause the top layer of concrete to become soft and brittle, leading to floor failure.
TECHNOLOGY	Our hybrid-polymer base is the newest technology, designed specifically for residential application.	High-solvent based epoxies use a fifty-plus year old technology which is prone to ambering.
COMPONENTS	Our products have extremely low VOCs (volatile organic compounds) and are non-hazardous and environmentally friendly.	Competitors use hazardous materials with very harsh odors. These products have a high solvent content and are highly flammable.
GUARANTEE	Each garage floor system is backed by a written warranty against workmanship and material defects.	"Lifetime" warranties for floor coatings can be misleading. The fine print may exclude some products used during installation.



Steamboat Springs, CO 80487 970.846.7588